

©EPODOC/EPO

PN - JP57175247 A 19821028
PD - 1982-10-28
PR - JP19810060601 19810423
OPD - 1981-04-23
TI - RADIATION VOID FACTOR METER
IN - NARABAYASHI SUNAO
PA - TOKYO SHIBAURA ELECTRIC CO
EC - G01N23/12
IC - G01N23/02
CT - US3350564 A []; JP40012718U U []; JP49108896 A []

©PAJ/JPO

PN - JP57175247 A 19821028
PD - 1982-10-28
AP - JP19810060601 19810423
IN - NARABAYASHI SUNAO
PA - TOKYO SHIBAURA DENKI KK
TI - RADIATION VOID FACTOR METER
AB - PURPOSE: To measure the void factor of a double layer current in a quick and accurate way, by carrying out a radiation beam scan via plural slits provided on a rotary disk.
- CONSTITUTION: A cylindrical measuring part 1 of a pipe in which a double phase current of a vapor phase like the high temperature and high pressure steam of a reactor, a boiler, etc. and a liquid phase like water, etc. is irradiated by an X-ray radiation beam given from a radiation source 2. The X-ray radiation beam corresponding to the void factor corresponding to the ratio between the vapor phase the liquid phase is detected by a radiation detector 3 through a number of slits 10 on a disk 9 which turns in a constant speed. In such constitution, the section of the part 1 is scanned by the X-ray radiation beam from the lower part to the part. Thus a local factor distribution is measured in a quick and accurate way. As a result, the section mean void factor can be assuredly decided even in the high-speed transient mode.
I - G01N23/02